

Technical Specifications⁺

| recinited open | | | | | |
|--------------------|-----------------------|-------------------|----------------------|---------------------------|------------------------------|
| BODY DIMENSIONS | | Max Net Power | 5.86 Kw (8bhp) | Rim Size (Front) | 10 inch |
| Length | 1761 mm | | @7500 rpm | Rim Size (Rear) | 10 inch |
| Width | 710 mm | Max Net Torque | 9 Nm @5500 rpm | Brake Type & Size (Front) | Drum 130mm |
| Height | 1149 mm | Bore Stroke | 50 mm 55.6 mm | Brake Type & Size (Rear) | Drum 130mm (CBS) |
| Wheel Base | 1238 mm | Compression Ratio | 9.5:1 | FRAME & SUSPENSION | |
| Ground Clearance | 153 mm | Air Filter Type | Viscous Paper Filter | Frame Type | Under Bone |
| Seat Height | 765 mm | Starting Method | Kick/Self | Front | Spring Loaded Hydraulic Type |
| Kerb Weight | 108 kg | TRANSMISSION | | Rear | Spring Loaded |
| Fuel Tank Capacity | 5.3 L | Туре | V - Matic | | Hydraulic Type |
| ENGINE | | Max Speed | 83 kmph | ELECTRICALS | |
| Type | Fan Cooled, 4 Stroke, | TYRES & BRAKES | | Battery | 12V 3Ah |
| | SI, BS-IV Engine | Tyre Size (Front) | 90/100-10 (Tubeless) | | (Maintenance Free) |
| Cylinder Capacity | 109.19 CC | Tyre Size (Rear) | 90/100-10 (Tubeless) | Head Lamp | 12V 35/35W |

1. Activa 4G meets Bharat Stage IV norms. 2. ⁺The technical specifications and design of the scooter shown here may vary according to the requirements and conditions and are subject to change without any notice. 3. *Accessories shown in the picture are not a part of the standard equipment. 4. **Conditions apply.










Authorised Dealer



Honda Motorcycle and Scooter India Pvt. Ltd., Registered Office: Commercial Complex II, Sector - 49-50, Golf Course Extension Road, Gurgaon - 122018 (Haryana), India; Website: www.hondazwheelersindia.com Customer Care: customercare@hondazwheelersindia.com





